

ASCENT X²

16-X2 CELLULAR MULTI-TENANT TELEPHONE ENTRY SYSTEM WITH KEYPAD

FEATURES

- Custom user-printed directory insert
- Professionally etched stainless-steel directory insert*
- Control via app, text, voice, directory call, or keypad
- Cloud-based access control management
- Remote management of up to 1,000 keypad codes†
- Up to 10,000 app, text, and voice users
- Rollover calling—up to 3 phone numbers per user
- Broadcast calling—up to 10 phone numbers per user
- Location-Based Access Control (LBAC)
- Push notifications and/or event/status emails
- Nightlight, valet light, and lighted keypad
- Amazon Alexa® integration

* A coupon for a complimentary professionally etched directory insert is included with every unit.



powered by  **SUMMIT CONTROL**

CALLING MADE EASY

Key in the directory code listed by the resident you wish to call and the unit calls.

CUSTOM-MADE DIRECTORY INSERT

Etched on stainless steel and set behind tamper-resistant glass, the directory is easily readable day or night and looks really nice.

LOCATION-BASED ACCESS CONTROL

Users must be within a defined distance from the unit to open the gate or entry door.

GET CONNECTED EVERY TIME

Assign multiple phone numbers to each user to be called in order or simultaneously and ensure a connection is always made.

 **SECURITY BRANDS INC**



MADE IN THE USA
FROM GLOBAL MATERIALS

SPECIFICATIONS

PHYSICAL

Dimensions	12-7/8"(H) x 6-1/2"(W) x 5-1/4"(D)
Shipping Weight	8 lbs.

ELECTRICAL

Input	12-24 VAC/DC 12-VDC transformer included
Current Draw	less than 170 mA @ 12 VDC less than 140 mA @ 24 VDC standby with nightlight and valet light less than 190 mA @ 12 VDC less than 160 mA @ 24 VDC with relay latched

RELAY






Contact Rating	10 A @ 120 VAC / 24 VDC
Max Switching Voltage	250 VAC / 30 VDC
Max Switching Current	15 A
Max Switching Power	240 W / 2,770 VA

ENVIRONMENTAL

Operating Temperature	-15 to 158 °F
-----------------------	---------------

▲ Actual voltage should be no more than 10% beyond specified range. Use of the included 12-VDC transformer is recommended.

CONTROL IT YOUR WAY

-  APP
-  TEXT
-  VOICE
-  DIRECTORY CALL
-  KEYPAD

OTHER GREAT FEATURES

- 7-day timers
- Holiday timers
- Special-event timers
- Temporary users with permission limits
- Quick temporary-user setup
- Audit trail with detailed reports
- "Do Not Disturb" mode
- Durable tempered-glass directory lens
- Stainless steel faceplate
- Powder-coated, galvanized steel enclosure

GET STARTED NOW!

PAY JUST ONE BILL!†

Unit includes a T-Mobile SIM card‡ ready for activation.

We do ALL the legwork for you!



SUMMIT CONTROL
it's that simple!



visit summitcontrol.com

† Because keypad codes are managed via Summit Control, keypad codes cannot be added or deleted without an active service plan.

‡ Monthly bill covers the cost of the SIM card, actions gateway, Summit Control servers, maintenance, development, and tech support.

§ A customer-supplied AT&T SIM card and service plan can be used, or an AT&T SIM card can be supplied during activation if needed.



Security Brands, Inc. Phone: (303) 799-9757
1675 W Yale Ave Toll-Free: (800) 541-5677
Englewood, CO 80110 Fax: (303) 799-9756

securitybrandsinc.com