

# PROX 2000 II

**23-206** POST-MOUNT PROXIMITY CARD READERS - HID

## FEATURES

- Allows up to 2,000 HID proximity cards
- Program up to 3 facility codes
- Wiegand input for second card reader
- "3 strikes, you're out" security
- Personal master code
- Latch card
- Sleep card
- True anti-passback
- 1,000-code transaction buffer
- Two relays with split-relay function
- Variable relay time
- Non-volatile memory
- Audible tones and LED feedback
- Nightlight



## SIMPLE IS OUR NAME

These card readers couldn't be any easier to install, program, and use day in and day out.

## VERSATILITY IS OUR GAME

We offer both HID and SecuraKey readers in post-mount and surface-mount versions, with or without a keypad or intercom.

## STURDY & DURABLE

Crafted exclusively from stainless and powder-coated steel, these units will last!

## PROGRAMMING YOU KNOW

Quick, simple, and familiar, the keypad programming steps are similar to those on other Security Brands, Inc. keypads.

## SPECIFICATIONS

### PHYSICAL

Dimensions	6-5/8"(H) x 5-1/2"(W) x 4-1/4"(D)
Shipping Weight	5 lbs. 23-206
	7 lbs. 23-206i, 23-206kp

### ELECTRICAL

Input	16.5 VAC 16.5-VAC transformer included
Current Draw	less than 40 mA @ 12 VDC standby with nightlight
	less than 67 mA @ 12 VDC with relay latched

### RELAY

Contact Rating	1 A @ 24 V / .5 A @ 120 V DC Load / AC Load
Max Switching Voltage	150 V / 220 V
Max Carrying Current	2 A / 2 A
Max Switching Power	28 W / 60 VA
Variable Relay Time	1-99 seconds

### ENVIRONMENTAL

Operating Temperature	-15 to 175 °F
-----------------------	---------------



**23-206**  
CARD READER



**23-206i**  
CARD READER WITH INTERCOM



**23-206kp**  
CARD READER WITH KEYPAD

## AVAILABLE MODELS

MODEL	DESCRIPTION
23-206	card reader
23-206i	card reader with intercom
23-206kp	card reader with keypad